



SPECIALTY MACHINES

POCKET BUCKET



A UNIQUE MACHINE.

***A REMOTE CONTROLLED TRACKED SKID STEER,
EQUIPPED WITH A TELESCOPIC ARM AND A
BUCKET FOR SHOVELING IN DANGEROUS AREAS.***

VARMAN Heavy Equipments Private Limited

NO. 549, Sri Nilayam, 7th Main Road, NTI Layout, Near Sahakar Nagar, Hebbal, Bangalore-560097, INDIA.

Mobile - +91 86000 18612, +91 80504 81666 | Mail Id- office@dmvarman.com | www.dmvarman.com



TRANSPORTABLE

Unmatched transportability defines the **Pocketbucket**. Its lightweight, foldable design enables seamless stowage under truck beds, within vans, on trailers, or even inside aircraft. Integrated lifting points further enhance its versatility, facilitating crane or helicopter deployment.



ROBUST

High resistance steel rollers built with anti-track derailment system and grease tensioner.



SAFETY

The remote control integrates all movements through dual joystick. Driving and steering the tracks is extremely easy and precise with a single joystick. Precision movement and tilting of the mast is easy with the second joystick.



ALWAYS READY FOR ACTION

The Smart Battery System (SBS) is an integrated sealed compartment that houses a battery charger for the remote control. The spare battery recharges automatically while the machine is working.



INTUITIVE DRIVING

Simplified operations with the intuitive single-joystick system, granting the operator full control of machine movement while managing the accessories with a separate joystick with the other hand.



DURABILITY

The **Pocketbucket** is a specialty machine with an undercarriage built from high strength materials with a corrosion resistant coating.



Specialty Machines – POCKETBUCKET

TECHNICAL SPECIFICATIONS

Dry Weight	1730 kg
Lifting Capacity Retracted/Extended	800/500 kg
Lifting Height	284 cm
Engine	KUBOTA V1505
N. of Cylinders	3
Engine Power	24.8 hp / 18.5 kw
Engine Torque	92.6 Nm @ 1700 rpm
Emissions	Stage V - EPA Tier 4 Final
Fuel Tank	27 L Diesel
Cooling System	Liquid
Hydraulic Oil Tank Capacity	34 L
Transmission	Hydrostatic Proportional
Speed	8 km/h

© MDB Srl 2025 - Image, technical and construction specifications subject to change with no obligation of prior notification. All rights reserved.

